

Safety Data Sheet

Version 1

1. Identification of the Substance/Preparation and of the Company/Undertaking

Product Identifier Product name Chemical name

GLISTEN PROMISE FURNITURE POLISH WITH LEMON OIL 7-7937-2

Other means of identificationProduct codeFG 431-2525-3SynonymsFurniture Polish

Recommended use of the chemical and restrictions on useRecommended UseWood cleaner and protectant.Uses advised againstDO NOT USE ON FLOORS

Details of the supplier of the safety data sheetSupplier AddressFulton Distributing53603 Polk StreetCoachella, CA 92236760-262-6200Emergency Telephone NumberCompany Phone Number708-865-100024 Hour Emergency Phone Number1-800-255-3924

Manufacturer Address

Chase Products Co. 2727 Gardner Road Broadview, IL 60155 708-273-1121

2. Hazards Identification

Classification

Acute toxicity - Inhalation (Gases)	Category 4
Aspiration toxicity	Category 1
FLAMMABLE AEROSOLS	Category 2
Gases Under Pressure	liquefied gas

Label Elements

EMERGENCY OVERVIEW

DANGER		
hazard statements HARMFUL IF INHALED		
May be fatal if swallowed and enters airways		
Flammable Aerosol		
Contains gas under pressure; may explode if h	heated	
Appearance White, creamy emulsion.	Physical State Aerosol	Odor Lemon

Precautionary Statements - Prevention

Avoid breathing fumes, mist, vapors or spray. Use only outdoors or in a well-ventilated area Keep away from heat, sparks, open flames and hot surfaces. — No smoking Do not spray on an open flame or other ignition source Pressurized container: Do not pierce or burn, even after use

Precautionary Statements - Response

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing Call a POISON CENTER or doctor if you feel unwell IF SWALLOWED: Immediately call a POISON CENTER or doctor Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up Protect from sunlight. Store in a well-ventilated place Do not expose to temperatures exceeding 122 °F (50 °C)

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other Information

Toxic to aquatic life with long lasting effects

- · Harmful to aquatic life
- -

3. 0	Compositior	n/information	on Ingredients
------	-------------	---------------	----------------

Synonyms	
Chemical Family	
Formula	

Furniture Polish. MIXTURES. 7-7937-2

Chemical name	CAS No	weight-%	Trade secret
Water	7732-18-5	70-75	*
Isoparaffinic Hydrocarbon	64742-47-8	5-10	*
Propane	74-98-6	1-5	*
Naphtha (petroleum), light alkylate	64741-66-8	1-5	*
n-butane	106-97-8	1-5	*

* The exact percentage (concentration) of composition has been withheld as a trade secret.

4. First aid measures

FIRST AID MEASURES Eye Contact

Skin contact

Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice.

In case of contact, immediately flush skin with plenty of water. Wash skin with soap and water. If irritation develops, consult a physician.

inhalation If overcome by vapor, move person to fresh air. If person is not breathing, call 911 or an ambulance, then provide artifical respiration, preferably mouth-to-mouth, if possible. Call a poison control center or doctor for further treatment advise.

INGESTION Ingestion from an aerosol product is unlikely to occur. Contains petroleum distillates. Harmful if swallowed. If accidentally swallowed, do not induce vomiting, call physician immediately.

Most important symptoms and effects, both acute and delayed

Symptoms	Acute: Prolonged inhalation of concentrated vapor or mist may cause headaches, dizziness and nausea. Prolonged and repeated contact with skin may cause irritation and reddening. Contact with eyes causes irritation.	
Indication of any immediate medical attention and special treatment needed		
Note to physicians	Contains petroleum distillates, do not induce vomiting because of aspiration neumonia hazard.	

5. Fire-fighting measures

Suitable extinguishing media

Dry chemical, CO2 or water spray.

Unsuitable extinguishing media Caution: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

This product is under pressure. Water spray may be used to cool cans in the vicinity of fire or excessive heat to prevent the explosion of the cans.

Hazardous combustion products Thermal decomposition may release carbon monoxide and carbon dioxide.

Explosion data

Sensitivity to Mechanical Impact Contents under pressure, keep away from heat and open flame.

Sensitivity to Static Discharge Keep away from heat, sparks, flame, and other sources of ignition (i.e., pilot lights, electric motors and static electricity).

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. Accidental release measures	
Personal precautions, protective e	quipment and emergency procedures
Personal precautions	Use with adequate general or local exhaust ventilation.
For emergency responders	Remove all sources of ignition.
Environmental Precautions	
Environmental Precautions	See Section 12 for additional Ecological Information.
Methods and material for containment and cleaning up	
Methods for Containment	Provide adequate ventilation to area being treated. Soak up spills with chemically inert, absorbent material.
Methods for cleaning up	Clean contaminated surface thoroughly.
7. Handling and Storage	
Precautions for safe handling	
Advice on safe handling	Do not deliberately inhale vapor or spray mist. Avoid getting spray into eyes. Keep out of reach of children.
Conditions for safe storage, including any incompatibilities	

FG 431-2525-3 GLISTEN PROMISE FURNITURE POLISH WITH LEMON OIL

Storage Conditions

Store in a cool, dry place away from heat and open flame. Keep out of reach of children. AEROSOL STORAGE LEVEL I (NFPA-30B).

Incompatible Materials

Avoid heat, open flame and contact with strong oxidizers.

8. Exposure Controls/Personal Protection

Control parameters

Exposure guidelines

See occupational exposure limits listed below.

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Propane 74-98-6	TWA: 1000 ppm	TWA: 1000 ppm TWA: 1800 mg/m ³ (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m ³	IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m³
n-butane 106-97-8	STEL: 1000 ppm	(vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m ³	TWA: 800 ppm TWA: 1900 mg/m ³

Appropriate engineering controls

Engineering controls	Use with adequate general or local exhaust ventilation.
Individual protection measures, su	ch as personal protective equipment
Eye/face Protection	Conventional eyeglasses to guard against splashing.
Skin and Body Protection	Household type gloves.
Respiratory protection	None required if used in a well-ventilated area .
General hygiene considerations	Wash hands thoroughly after handling.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Physical State Appearance Color	Aerosol White, creamy emulsion. white	Odor Odor threshold	Lemon No information available
<u>Property</u> pH	<u>Values</u> Not applicable	Remarks • Method Water-oil emulsion.	
Melting point/freezing point	Not applicable	No information available	
Boiling point/boiling range	Water 212 °F/100 °C	No information available	
Flash Point	Not Available. This is an aerosol	No information available	
	product for which Flame Projection is	0	
	inches. Temperatures above 120 F		
E su sud su Bada	may cause cans to burst.		
Evaporation Rate	Faster than butyl acetate	No information available	
Flammability (solid, gas)		No information available	
Flammability Limits in Air		No information available	
Upper flammability limits	Not available		
Lower Flammability Limit	Not available		
Vapor pressure		No information available	
Vapor Density		No information available	
Relative Density	0.93 to 0.95 g/ml concentrate	No information available	
Water solubility	Insoluble in water	No information available	
Solubility in other solvents		No information available	
Partition coefficient		No information available	
Autoignition Temperature		No information available	
Decomposition temperature		No information available	

Kinematic viscosity Dynamic viscosity Explosive properties Oxidizing properties

Other Information

Softening point Molecular weight VOC content (%) Density Bulk Density No information available No information available

No information available No information available 11.57% 7.83 lb/gal No information available

10. Stability and Reactivity

No information available

No information available

Reactivity Not applicable

no data available

 Chemical stability

 Stable.

 Possibility of hazardous reactions

 Temperatures above 130 °F may cause cans to burst with force.

 hazardous polymerization

 Hazardous polymerization does not occur.

<u>Conditions to Avoid</u> Temperatures above 122 °F (50 °C). <u>Incompatible Materials</u> Avoid heat, open flame and contact with strong oxidizers. <u>Hazardous decomposition products</u> Thermal decomposition may yield gases like carbon monoxide and carbon dioxide.

11. Toxicological Information

Information on likely routes of exposure

Product Information This product has not been tested as whole. See below for information on ingredients.

inhalation no data available.

Eye Contact no data available.

Skin contact no data available.

INGESTION no data available.

Chemical name	Oral LD50	dermal LD50	Inhalation LC50
Water 7732-18-5	> 90 mL/kg (Rat)	-	-
Isoparaffinic Hydrocarbon 64742-47-8	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat)4 h
Propane 74-98-6	-	-	= 658 mg/L (Rat)4 h
Naphtha (petroleum), light alkylate 64741-66-8	> 7000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.04 mg/L (Rat)4 h
n-butane 106-97-8	-	-	= 658 g/m³(Rat)4 h

Information on toxicological effects

Symptoms

Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Serious eye damage/eye irritation irritation corrosivity sensitization Germ Cell Mutagenicity carcinogenicity	May cause irritation after prolonged contact with skin. Irritating to eyes. May cause skin and eye irritation. Not applicable. No information available. No information available. Not known chronic effects based on available data. None of the ingredients present in excess of 0.1% are listed as carcinogenic by NTP, IARC or OSHA.	
Reproductive Toxicity	No information available.	
STOT - single exposure	No information available.	
STOT - repeated exposure	No information available.	
Aspiration Hazard	No information available.	
Numerical measures of toxicity - Product Information		
Unknown acute toxicity	•	
The following values are calculated	based on chapter 3.1 of the GHS document .	
ATEmix (oral)	35844 mg/kg	
ATEmix (dermal)	11099 mg/kg	
ATEmix (inhalation-gas)	17560 mg/l	
ATEmix (inhalation-dust/mist)	3.2 mg/l	
ATEmix (inhalation-vapor)	37 mg/l	
12. Ecological Information		

This product contains a chemical which, although not listed, meets the IMDG criteria for being a marine pollutant.

ecotoxicity

14.14% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical name	Algae/aquatic plants	Fish	Toxicity to Microorganisms	Crustacea
Isoparaffinic Hydrocarbon 64742-47-8		45: 96 h Pimephales promelas mg/L LC50 flow-through 2.4: 96 h Oncorhynchus mykiss mg/L LC50 static 2.2: 96 h Lepomis macrochirus mg/L LC50 static		4720: 96 h Den-dronereides heteropoda mg/L LC50
Naphtha (petroleum), light alkylate 64741-66-8	30000: 72 h Pseudokirchneriella subcapitata mg/L EC50			2: 48 h Mysidopsis bahia mg/L LC50

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical name	Partition coefficient
Propane 74-98-6	2.3
n-butane 106-97-8	2.89

Other adverse effects

No information available

13. Disposal Considerations

Waste treatment methods	
Disposal of wastes	Dispose of in accordance with federal, state and local regulations.
Contaminated packaging	Pressurized container: Do not pierce or burn, even after use. Do not puncture or incinerate container. If empty: Place in trash or offer for recycling if available. If partly filled: Call your local solid waste agency for disposal instructions.

14. Transport Information

DOT

Image: T_______Limited quantity (LQ) Furniture PolishUN/ID noUN1950Proper Shipping NameLimited quantity (LQ)Hazard Class2.1Marine pollutantThis product contains a chemical which, although not listed, meets the IMDG criteria for being a marine pollutant.

15. Regulatory information

International Inventories TSCA

All ingredients of this product are listed or are excluded from listing under the U.S. Toxic Subtances Control Act (TSCA) Chemical Substance Inventory. All ingredients are listed or are excluded from listing on the DSL.

DSL Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

yes

SARA 311/312 Hazard Categories	
Acute Health Hazard	
Chronic Health Hazard	

Chronic Health Hazard	No
Fire Hazard	yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Water 7732-18-5			X
Propane 74-98-6	X	X	X
n-butane 106-97-8	X	X	X

U.S. EPA Label information

EPA Pesticide registration number Not applicable

16. Other information				
<u>NFPA</u>	Health Hazards 1	Flammability 1	Instability 1	Physical and chemical properties Not applicable
<u>HMIS</u>	Health Hazards 1	Flammability 2	Physical Hazards 1	Personal Protection B - Eyes and hands protection
Prepared by Issue date Revision note	Regulatory Department 13-Jul-2015			

This SDS supersedes a previous MSDS dated December 17, 2012.

Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet