

acrylic-based floor finish

The pinnacle of the Millennia Bright Laminate System, Dura Gloss Laminate, transforms and improves traditional acrylicbased floor finish technology. The durable, brilliant clear gloss laminate offers easy application, repair and removal.



Providing Quality Maintenance and Chemical Specialty Solutions with Unparalleled Customer Service



Spartan Chemical Company, Inc. 1110 Spartan Drive Maumee, OH 43537 1-800-537-8990 www.spartanchemical.com

ENGINEERED FOR EASE OF APPLICATION:

While a thin, uniform coat of traditional finish will nearly always produce the best results, this laminate is formulated for flexibility. Its excellent leveling and quick dry time provide a forgiving, mistake proof nature that tolerates thick, thin or in-between application. Dura Gloss gives you a simply beautiful floor without fish eyes, bubbles or lap marks.

HIGH LEVEL APPEARANCE:

Create a pure, crystal clear gloss with brilliant shine. It's excellent clarity allows the natural color of flooring to pass through the laminate unobstructed. Even areas with no windows look lighter and brighter. It is non-yellowing, even after repeated re-coats.

TOUGH, DURABLE LAMINATE:

Dura Gloss Laminate is 21st Century acrylic polymer emulsion technology. The formula's ionic cross-linked bond provides a tough, durable surface to prevent damage and deterioration due to abrasion, scratching, scuffing, black heel marks and wear.

VERSATILE:

This product can be applied with any application method, to nearly every hard floor surface. Maintain with conventional, high speed and ultra-high speed equipment.

EASY TO MAINTAIN:

This system requires little, if any, damage control. For example, a simple, routine floor maintenance procedure could entail dust and damp mop weekly; top scrub monthly; and deep scrub and re-coat as required.



DIRECTIONS FOR USE:

Some individuals may be sensitive to ingredients in this product. Before use, read product label and MSD sheet. Wet floors may be slippery. Prevent pedestrian traffic with signs or barricades.

INITIAL APPLICATION:

- Completely strip all old wax or floor finish. Use warm or room temperature water (80°-120°F) and a Spartan stripper.
- 2. Remove the stripping solution and follow with two to three clear-water rinses.
- 3. When flooring is old, abused or damaged, two coats of Millennia Bright Dura Prime is recommended.
- 4. Apply Dura Gloss Laminate in a uniform coat. Let dry thoroughly for 30 to 40 minutes until surface is dry to the touch. Apply subsequent coats in the same manner. Three to five coats are recommended.

MAINTENANCE:

Routine: Dust mop and damp mop with a Spartan neutral cleaner.

Periodic: Dust floor and damp mop with a Spartan neutral cleaner. To repair traffic areas between finish applications, use a Spartan restorer or spraybuff. Be careful to follow Directions for Use. (Traffic lanes may be recoated as necessary.)

As Needed: Deep scrub and recoat; or completely strip, reseal and reapply Dura Gloss Laminate. Be sure to read all Directions, Precautionary and First Aid Statements on product labels before use of this or any Spartan product. If questions remain, consult your employer or a physician. Material Safety Data Sheets for all Spartan products are available from your authorized Spartan distributor or by visiting www.spartanchemical.com.

SPECIFICATIONS:

Total Solids – 20.5% Non-Volatile Solids – 16% - 18% pH (Concentrate) – 8.5-9.0

Stability

- a. Storage @ 24°C/75°F One year minimum
- b. Accelerated @ 49°C/120°F 30 days minimum
- c. Freeze/Thaw Can withstand three cycles

Gloss (Gardner) a. 1 coat – 75-80

b. 2 coats - 85-90

Static coefficient of friction meets or exceeds 0.5 as determined by ASTM method D 2047.

COVERAGE:

Up to 3,000 square feet per gallon depending on application method and porosity of floor.

		No.
PACKAGING		
406060	275-gallon totes	
406055	55-gallon drum	
406030	30-gallon drum	5
406015	15-gallon drum	
406005	5-gallon pail	and the second s
406004	1-gallon (4 per case)	



GUARANTEE: Spartan's modern manufacturing and laboratory control insure uniform quality. If dissatisfied with performance of product, any unused portion may be returned for credit within one year of the date of manufacture. Use product as directed and read all precautionary statements.



Dura GLOSS