



high solids floor finish and sealer

You have high standards and shrinking budgets. We have The Fixx...a premium 25% high solids floor finish that contains patented optically enhanced polymer technology to create depth of gloss and remarkable clarity.

The state-of-the-art formulation provides total protection and long lasting response to burnishing, which dramatically extends your time between re-coats and strip outs... saving you labor while your facility boasts beautiful floors!





Spartan Chemical Company, Inc.
 1110 Spartan Drive
 Maumee, OH 43537
 1-800-537-8990
 www.spartanchemical.com

EXCELLENT GLOSS AND CLARITY:

The Fixx creates a clear, bright, non-yellowing gloss on floors. Its initial deep gloss increases over time in response to burnishing. Your result is a durable, burnishable finish with high shine and long life.

EASY TO APPLY AND MAINTAIN:

The Fixx levels easily and provides faster dry times with more tolerance to high relative humidity. The rapid recoat high solids formula is applied with minimal effort and quickly builds without developing mop marks or ridges.

TREMENDOUS LABOR SAVINGS:

The Fixx maintains long lasting response and extends the time between recoats by as much as 5 months and strip-outs by 18 months. Users benefit from low in-use costs due to the labor savings and long lasting response. The Fixx repels scuff marks, scratches, water marks and wear. Since The Fixx has built-in high and ultra high speed buffing response, traffic damage is easily erased and gloss restored.

TESTED AND PROVEN EFFECTIVE:

In a six month test of The Fixx and several competitive products, The Fixx out-performed the competition in initial gloss, wear resistance and gloss retention.

The competitive products showed more traffic and wear patterns, both before and after burnishing; thus illustrating the balance of strength and reparability.

At the end of the six month study, The Fixx maintained a gloss reading 10% higher than the competition, an increase visible to the naked eye. Not only did this long term gloss outshine the competition, but it even beat its own initial gloss rating!

Distributed by:

SPECIFICATIONS:

- Total Solids – 34.5%
- Non-Volatile Solids – 25%
- Stability
 - a. Storage @ 24°C / 75°F – one year minimum
 - b. Accelerated @ 49°C / 120°F – 60 days minimum
 - c. Freeze / Thaw – can withstand three cycles
- Gloss (Gardner)
 - a. One coat – 90
 - b. Two coats – 95
- Static coefficient of friction meets or exceeds 0.5 as determined by ASTM method D-2047

COVERAGE:

2,000 – 3,000 square feet per gallon depending on application method and porosity of floor.

MAINTENANCE:

Dust mop with Spartan’s Dust Mop/Dust Cloth Treatment™ and damp mop with Spartan Damp Mop™ or DMQ® Neutral Disinfectant Cleaner.

Depending on traffic, high speed burnish as necessary to repair minor scratches and enhance gloss. Deep scrub as required with Shinline Multi Surface Cleaner and rinse with clear water prior to recoating. Depending on machine type and speeds, experiment with buffing pads for quick touch ups of high traffic or “first impression” areas. Note: For best results, always use Spartan floor cleaners and strippers.

DIRECTIONS FOR USE:

Wet floors may be slippery. Prevent pedestrian traffic with signs or barricades. Some individuals may be sensitive to ingredients in this product. Before using, read product label and MSD sheet.

If questions remain, consult your employer or a physician. Material Safety Data Sheets for all Spartan products are available from your authorized Spartan distributor or by visiting www.spartanchemical.com.

Initial Application:

1. Gather all necessary supplies and apply personal protective equipment as called for on the product’s MSDS.
2. Completely strip all old floor finish. Depending upon build-up, use warm or room temperature water [80°F-120°F / 27°C-49°C] and the Spartan stripper of your choice.
3. Remove all stripping solution and follow with two to three clear water rinses.
4. When flooring is old, abused or damaged, we recommend two coats of a Spartan sealer, although The Fixx may be used as a Self-sealing finish.
5. Apply finish in a uniform coat. Let dry thoroughly for 30 to 40 minutes until surface is dry to the touch. Apply subsequent coats in the same manner. Two to four coats are recommended.

PACKAGING	
404665	330-gallon totes
404660	275-gallon totes
404655	55-gallon drum
404630	30-gallon drum
404615	15-gallon drum
404605	5-gallon pail
404604	1-gallon (4 per case)



Label copy is available in English, Spanish and French. Secondary labels are also available.

GUARANTEE: Spartan’s modern manufacturing and laboratory control insure uniform quality. If dissatisfied with performance of product, any unused portion may be returned for credit within one year of the date of manufacture. Use product as directed and read all precautionary statements.

Product Available Worldwide. For institutional and industrial use only.

© SCC 11/10